


**Roller D6** 0.0.356.03

St, 100 Cr 6, hardened, polished  
Double ball bearing, shielded, maintenance-free


C [N]	C <sub>0</sub> [N]	n <sub>max</sub> [min <sup>-1</sup> ]	m [g]
1,620	780	10,000	8.0



**Roller D10** 0.0.442.02

St, 100 Cr 6, hardened, polished  
Double ball bearing, shielded, maintenance-free  
Washer, St, bright zinc-plated

C [N]	C <sub>0</sub> [N]	n <sub>max</sub> [min <sup>-1</sup> ]	m [g]
4,400	2,470	7,500	28.0



**Roller D14** 0.0.294.03

St, 100 Cr 6, hardened, polished  
Double ball bearing, shielded, maintenance-free

C [N]	C <sub>0</sub> [N]	n <sub>max</sub> [min <sup>-1</sup> ]	m [g]
7,800	4,400	5,000	100.0

**Roller D14K** 0.0.294.52


St, 100 Cr 6, hardened, polished  
Double ball bearing, shielded, maintenance-free  
Also corrosion-resistant and coated

C [N]	C <sub>0</sub> [N]	n <sub>max</sub> [min <sup>-1</sup> ]	m [g]
7,800	4,400	5,000	100.0

**Roller D14, stainless** 0.0.488.20

St, X 105 Cr Mo 17, hardened, polished  
Double ball bearing, shielded, maintenance-free

C [N]	C <sub>0</sub> [N]	n <sub>max</sub> [min <sup>-1</sup> ]	m [g]
6,200	3,500	5,000	100.0



**Roller D25** 0.0.350.03

St, 100 Cr 6, hardened, polished  
Double ball bearing, shielded, maintenance-free

C [N]	C <sub>0</sub> [N]	n <sub>max</sub> [min <sup>-1</sup> ]	m [g]
25,000	15,300	2,500	590.0